



## Excavators / E32 Compact Excavator

# Specifications & Options

■ Standard
  Optional
N/A Not Applicable

Units **Metric**

### Bobcat E32 25 HP

Emissions Tier (EPA)	Tier 4
Engine Fuel	Diesel
Maximum Governed RPM	2,200 rpm
Horsepower	18.5 kW
Turbocharged Engine	N/A
Optional Horsepower	n/a

### Performance

Operating Weight	3258 kg
Weight Class	3.3 t
Travel Speed - High	4.7 km/h
Travel Speed - Low	2.6 km/h
Arm Digging Force	20,413 N
Bucket Digging Force	31,000 N
Rated Lift Capacity	1347 kg
Lift Radius	2997 mm
Boom Swing - Left	75°
Boom Swing - Right	55°
Maximum Dig Depth	3.1 m
Max Dump Height	3.4 m
Maximum Reach at Ground Level	5 m

### Capacities

Fuel Tank	51.9 l
-----------	--------

### Hydraulic System

Auxiliary Std Flow	64 l/min
Auxiliary Pressure	205.95 bar

## Dimension

Length	4661 mm
Overall Length in Travel Position	4661 mm
Width	1549 mm
Height	2443 mm
Height with Operator Cab	2443 mm

## Features

Air Conditioning	<input checked="" type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Heater Air Conditioning	<input checked="" type="checkbox"/>
Radio	<input checked="" type="checkbox"/>
Tail Swing Type	Conventional
Engine Shutdown	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Secondary Auxiliary Hydraulics	<input checked="" type="checkbox"/>
Quick Tach System	<input type="checkbox"/>
Rubber Track	<input type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input type="checkbox"/>
Angle Blade	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.